

Excelsior Epoxy Wet Set Adhesive

Version Revision Date: MSDS Number: Date of last issue: -

1.0 8/23/2016 EW-710 – Part B Date of first issue: 03/04/2016

SECTION 1. IDENTIFICATION

Product name : Excelsior EW-710 - Part B

Product Description : Epoxy Wet Set Adhesive

Supplier : RHC

Address : 1602 N. Union St.

Fostoria, OH 44830

Telephone : (844) 393 - 4044

Fax : (419) 436 - 2482

Emergency Telephone : CHEMTREC: 1 (800) 424-9300

Number CANUTEC: (613) 996 - 6666

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification : H315 – Skin Irrit. 2

H317 – Skin Sens. 1 H318 – Eye Dam. 1 H411 – Aquatic Chronic 2

See section 16 for full text of H-Phrases

GHS Label Elements

Hazard Pictograms :



Signal Word : Danger

Hazard Statements : H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary Statements: P260 - Do not breathe vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas

thoroughly after handling.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, and eye

protection.

P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT

induce vomiting.

P303+P361+P353 - IF ON SKIN (OR HAIR): Take off



Excelsior Epoxy Wet Set Adhesive

Version Revision Date: MSDS Number: Date of last issue: -

1.0 8/23/2016 EW-710 – Part B Date of first issue: 03/04/2016

immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340 - IF INHALED: Remove person to fresh air and

keep at rest in a position comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

Other Hazards : Exposure may aggravate those with pre-existing eye, skin or

respiratory conditions.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Classification : Mixtures

Description : Adhesive

Hazardous Components

CAS#	Chemical Name	Percentage
68082-29-1	Fatty acids, C18-unsaturated, dimers, polymers with tall-oil fatty acids and triethylenetetramine	15 - 40
27138-31-4	Propanol, oxybis-, dibenzoate	3-7
90-72-2	2,4,6-Tri(dimethylaminomethyl)phenol	3-7
112-57-2	Tetraethylenepentamine	3-7
112-24-3	Triethylenetetramine	1 – 5
14808-60-7	Quartz*	0.1 – 1.0

^{*}This product contains a material that may be hazardous when present as an airborne dust. Since this product is in a liquid form, the material is not able to become airborne and cannot be inhaled. Thus, the hazards usually associated with this material are not applicable to this product.

SECTION 4. FIRST AID MEASURES

First Aid Measures

General : Never give anything by mouth to an unconscious person. If

you feel unwell, seek medical advice (show the label if

possible).

Inhalation : If inhaled, move to fresh air and keep at rest in a position

comfortable for breathing. Seek medical advice if breathing

difficulty persist.

Skin Contact : In case of skin contact, flush with plenty of water for at least

60 minutes while. Remove all contaminated clothing and wash before reuse. Call a POISON CENTER or doctor/physician if

you feel unwell.



Excelsior Epoxy Wet Set Adhesive

Version Revision Date: MSDS Number: Date of last issue: -

1.0 8/23/2016 EW-710 – Part B Date of first issue: 03/04/2016

Eye Contact : In case of eye contact, rinse cautiously with plenty of water for

at least 60 minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Seek medical attention

immediately.

Ingestion : If swallowed, do not induce vomiting. If conscious, rinse out

mouth and drink plenty of water. Contact a POISON CENTER

or doctor/physician immediately.

Most Important Symptoms and effects, Both Acute and Delayed

General : Causes severe skin burns and eye damage. May cause an

allergic reaction in sensitive individuals.

Inhalation : May cause respiratory irritation.

Skin Contact : Contact may cause immediate severe irritation progressing

quickly to chemical burns. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis. May

cause an allergic reaction in sensitive individuals.

Eye Contact: Serious damage to eyes. Symptoms may include: Redness,

pain, swelling, itching, burning, tearing, and blurred vision.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms : None known.

Indications of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical attention (show product label where possible).

SECTION 5. FIREFIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing

Media

: Use extinguishing media appropriate for area.

Unsuitable Extinguishing

Media

: Do not use heavy water stream, as this may spread fire.

Specific Hazards Arising From Substance or Mixture

Fire Hazard : Product is not flammable.

Explosion Hazard : Product is not explosive.

Reactivity : Hazardous polymerization can occur on heating.



Excelsior Epoxy Wet Set Adhesive

Version Revision Date: MSDS Number: Date of last issue: -

1.0 8/23/2016 EW-710 – Part B Date of first issue: 03/04/2016

Advice for Firefighting

Precautionary Measures While Firefighting

: Exercise caution when fighting any chemical fire. Under fire

conditions, hazardous fumes may be present.

Specific Firefighting Instructions

: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Do not allow run-off from firefighting to enter sewage systems or water course.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Specific Protection Equipment for Firefighters Do not enter fire area without proper protective equipment,

including respiratory protection.

Hazardous Combustion Products

: Under fire conditions this material may produce hazardous carbon dioxide (CO2), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke. Nitrogen oxides.

Amines. Ammonia.

Other Information : Refer to Section 9 for flammability properties.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment & Emergency Procedures

General Measures : Avoid all contact with skin, eyes or clothing. Do not breathe

vapor, mist or spray. Use only outdoors or in a well-ventilated area. Do not allow product to spread into the environment.

Instructions for Non-Emergency Personnel : Use appropriate personal protection equipment (PPE).

Evacuate unnecessary personnel.

Instructions for Emergency

Personnel

Equip cleanup crew with proper protection. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area and call for assistance of trained personnel as soon

as conditions permit.

Environmental Precautions : Do not allow product to reach sewage systems or water

course. Inform respective authorities in case of seepage into

sewage or water course.

Methods & Materials for Containment and Cleaning

Up

: Contain any spills with dikes or inert absorbent material (e.g. sand, diatomite, universal binder, sawdust, etc.) to prevent migration into sewage systems and water course.

Clean up spills immediately and dispose of contaminated material according to section 13. Clean contaminated floors and objects thoroughly while observing environmental

regulations. Inform respective authorities in case of seepage

into sewage or water course.



Excelsior Epoxy Wet Set Adhesive

Version Revision Date: MSDS Number: Date of last issue: -

1.0 8/23/2016 EW-710 – Part B Date of first issue: 03/04/2016

Reference to Other

Sections See section 13 for disposal information.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When

Processed

: Hazardous polymerization may occur if exposed to high temperature. Product to be handled in a closed system and

See Section 8 for information on personal protection.

under strictly controlled conditions.

Hygiene Measures : Handle in accordance with industrial hygiene best practices

and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking

and when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures : Any proposed use of this product in elevated-temperature

processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. Comply

with applicable regulations.

Storage Conditions : Store in a dry, cool and well-ventilated area. Keep container

closed when not in use. Keep in fireproof place. Keep/Store away from direct sunlight, extremely high or low temperatures

and incompatible materials.

Incompatible Materials : Strong acids, strong bases, strong oxidizers. Nitrogen

containing compounds, ammonium compounds.

Specific End Use(s) : No use specified.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with Workplace Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m³)	0.025 mg/m³ (respirable fraction)
USA OSHA	OSHA PEL (STEL) (mg/m³)	250 mppcf/%SiO ₂ +5, 10mg/m ³ /%SiO ₂ +2
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.05 mg/m³ (respirable dust)



Excelsior Epoxy Wet Set Adhesive

Version Revision Date: MSDS Number: Date of last issue: -

1.0 8/23/2016 EW-710 – Part B Date of first issue: 03/04/2016

USA IDLH	US IDLH (mg/m³)	50 mg/m³ (respirable dust)
Alberta	OEL TWA (mg/m³)	0.025 mg/m³ (respirable particulate)
British Columbia	OEL TWA (mg/m³)	0.025 mg/m³ (respirable)
Manitoba	OEL TWA (mg/m³)	0.025 mg/m³ (respirable fraction)
New Brunswick	OEL TWA (mg/m³)	0.1 mg/m³ (respirable fraction)
Newfoundland & Labrador	OEL TWA (mg/m³)	0.025 mg/m³ (respirable fraction)
Nova Scotia	OEL TWA (mg/m³)	0.025 mg/m³ (respirable fraction)
Nunavut	OEL TWA (mg/m³)	0.1 mg/m³ (respirable mass)
Northwest Territories	OEL TWA (mg/m³)	0.1 mg/m³ (respirable mass)
Ontario	OEL TWA (mg/m³)	0.10 mg/m³ (designated substances regulation-respirable)
Prince Edward Island	OEL TWA (mg/m³)	0.025 mg/m³ (respirable fraction)
Québec	VEMP (mg/m³)	0.1 mg/m³ (respirable dust)
Saskatchewan	OEL TWA (mg/m³)	0.05 mg/m³ (respirable fraction)
Yukon	OEL TWA (mg/m³)	300 particle/mL

Exposure Controls

Engineering Controls

: Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure, but are not required. Product to be handled under strictly controlled conditions. Ensure all national/local regulations are observed. Gas detectors should be used when toxic gases may be released. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits.

Environmental Exposure Controls

: Do not allow product to be released into the environment.

Consumer Exposure Controls

: Do not eat, drink or smoke during use.

Personal Protective Equipment



General: : Wear protective goggles, gloves and protective clothing. In case of insufficient ventilation, wear respiratory protection.

SAFETY DATA SHEET



Excelsior EW-710 - Part B

Excelsior Epoxy Wet Set Adhesive

Version Revision Date: MSDS Number: Date of last issue: -

1.0 8/23/2016 EW-710 – Part B Date of first issue: 03/04/2016

Respiratory Protection : If exposure limits may be exceeded or irritation is

experienced, use a NIOSH-approved respirator or self-

contained breathing apparatus.

Hand Protection : Wear chemically resistant protective gloves.

Eye Protection : Chemical goggles or safety glasses.

Skin & Body Protection : Wear suitable chemically resistant protective clothing.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Thick Liquid

Physical State : Liquid

Color : Clear

Odor : Amine Odor

Odor Threshold : No data available

pH : No data available

Evaporation Point : No data available

Melting Point / Range : No data available

Freezing Point : 32° F (0° C)

Boiling Point / Range : ~350° F (176.67° C)

Flash Point : >200° F (93° C)

Flammability : No data available

Auto-Ignition Temperature : No data available

Decomposition

Temperature

: No data available

Specific Gravity : 1.4

Water Solubility : No data available

Partition Coefficient

(Noctanol/Water)

: No data available

Viscosity : ~30,000 CPS



Excelsior Epoxy Wet Set Adhesive

Version Revision Date: MSDS Number: Date of last issue: -

1.0 8/23/2016 EW-710 – Part B Date of first issue: 03/04/2016

Explosion Data – : Not expected to present an explosion hazard due to

Mechanical Impact mechanical impact

Explosion Data – Static

Discharge

: Not expected to present an explosion hazard due to static

discharge

VOC Content : < 12 g/l (<0.1 lbs/gal)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Hazardous polymerization can occur on heating.

Chemical Stability : Stable under recommended handling and storage conditions

(see section 7)

Possibility of Hazardous

Reactions

: Hazardous polymerization will not occur.

Conditions to Avoid : Direct sunlight. Extremely high or low temperatures. Ignition

sources. Incompatible materials.

Incompatible Materials : Strong acids. Strong bases. Strong oxidizers. Amines.

Hazardous Decomposition

Products

: Under fire conditions this material may produce hazardous carbon dioxide (CO2), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke. Nitrogen oxides.

Ammonia. Amines.

SECTION 11. TOXICOLOGICAL INFORMATION

Toxicological Effects (Product)

Acute toxicity : Not classified.

LD50 / LC50 Data : Not available.

Skin Corrosion / Irritation: Causes skin irritation.

Serious Eye Damage /

Irritation

: Causes serious eye irritation.

Respiratory or Skin

Sensitization:

: May cause an allergic skin reaction.

Germ Cell Mutagenicity : Not classified

Teratogenicity : Not classified

Carcinogenicity : Not classified



Excelsior Epoxy Wet Set Adhesive

Version Revision Date: MSDS Number: Date of last issue: -

1.0 8/23/2016 EW-710 – Part B Date of first issue: 03/04/2016

Reproductive Toxicity : Suspected of damaging fertility or the unborn child (oral).

Aspiration Hazard : Not classified

Specific Target Organ Toxicity (Single or Repeated Exposure) : Not classified

Symptoms / Injuries After

Inhalation

: May cause respiratory irritation

Symptoms / Injuries After

Skin Contact

: Causes skin irritation. Symptoms may include: Redness, pain,

swelling, itching, burning, dryness, and dermatitis.

Symptoms / Injuries After

Skin Contact

: Causes serious eye irritation. Symptoms may include:

Redness, pain, swelling, itching, burning, tearing, and blurred

vision.

Symptoms / Injuries After

Skin Contact

: Ingestion is likely to me harmful or have adverse effects.

Chronic Symptoms : Suspected of damaging fertility or the unborn child (oral).

Toxicological Effects (Ingredients)

Acute toxicity :

Quartz (14808-60-7)		
LD50 Oral Rat	> 5000 mg/kg	
LD50 Dermal Rat	> 5000 mg/kg	
Fatty acids, C18-unsaturated, dimers, polymers with tall-oil fatty acids and		
triethylenetetramine (68082-29-1)		
LD50 Oral Rat	> 2000 mg/kg	
LD50 Dermal Rat	> 2000 mg/kg	
Triethylenetetramine (112-24-3)		
LD50 Oral Rat	2500 mg/kg	
LD50 Dermal Rabbit	550 mg/kg	
2,4,6-Tri(dimethylaminomethyl)phenol (90-72-2)		
LD50 Oral Rat 1000 mg/kg		
LD50 Dermal Rat	1280 mg/kg	
Tetraethylenepentamine (112-57-2)		
LD50 Oral Rat	2100 mg/kg	
LD50 Dermal Rabbit	660 µl/kg	
Quartz (14808-60-7)		
IARC Group	1	
National Toxicology Program (NTP) Status	Known Human Carcinogens.	



Excelsior Epoxy Wet Set Adhesive

Version Revision Date: MSDS Number: Date of last issue: -

1.0 8/23/2016 EW-710 – Part B Date of first issue: 03/04/2016

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Ecology - General : Harmful to aquatic life with long lasting effects.

Ecotoxicity :

Triethylenetetramine (112-24-3)	
LC50 Fish 1	570 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])
EC50 Daphnia 1	31.1 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	495 mg/l (Exposure time: 96 h - Species: Pimephales promelas)

Tetraethylenepentamine (112-57-2)	
LC50 Fish 1 420 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])	
EC50 Daphnia 1	24.1 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Persistence & Degradability : Not available

Bioaccumulative Potential

Triethylenetetramine (112-24-3)	
BCF Fish 1 (no bioaccumulation expected)	
Log Pow	-1.4

Tetraethylenepentamine (112-57-2)	
BCF Fish 1	(no bioaccumulation expected)
Log Pow	< 1

Mobility in Soil : Not available

Other Adverse Effects : None known

Other Information : Avoid release into the environment

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Sewage Disposal Recommendations

: Do not flush into surface water or sewer system.

Waste Disposal Recommendations

: Dispose of waste material in accordance with international, national, federal, state/provincial and local regulations.

Ecology – Waste Materials : Avoid release to the environment.



Excelsior Epoxy Wet Set Adhesive

Version Revision Date: MSDS Number: Date of last issue: -

1.0 8/23/2016 EW-710 – Part B Date of first issue: 03/04/2016

SECTION 14. TRANSPORT INFORMATION

In Accordance with DOT

Proper Shipping Name : CORROSIVE LIQUIDS, N.O.S. (2,4,6-

Tri(dimethylaminomethyl)phenol, Tetraethylenepentamine)

Hazard Class : 8

Identification Number : UN1760

Label Codes : 8

Packing Group : II

ERG Number : 171

Limited Quantitied : Packages having a volumetric capacity of no more than

1.0L/0.3 gallons and meeting the requirements of 49 CFR 173.154(b) are exempt from many of the DOT requirements for this classification. Each package must display the

following limited quantity label:

In Accordance with IMDG

Proper Shipping Name : CORROSIVE LIQUIDS, N.O.S. (2,4,6-

Tri(dimethylaminomethyl)phenol , Tetraethylenepentamine)

Hazard Class : 8

Identification Number : UN1760

Label Codes : 8

Packing Group : II

EMS-No. (Fire) : F-A

EMS-No. (Spillage) : S-B

Marine Pollutant : Marine Pollutant



Excelsior Epoxy Wet Set Adhesive

Version Revision Date: MSDS Number: Date of last issue: -

1.0 8/23/2016 EW-710 – Part B Date of first issue: 03/04/2016

In Accordance with IATA

Proper Shipping Name : CORROSIVE LIQUIDS, N.O.S. (2,4,6-

Tri(dimethylaminomethyl)phenol, Tetraethylenepentamine)

Packing Group : II

Hazard Class : 8

Identification Number : UN1760

Label Codes : 8

ERG Code (IATA) : 8L

In Accordance with TDG

Proper Shipping Name : CORROSIVE LIQUIDS, N.O.S. (2,4,6-

Tri(dimethylaminomethyl)phenol, Tetraethylenepentamine)

Packing Group : II

Hazard Class : 8

Identification Number : UN1760

Label Codes : 8

Marine Pollutant : Marine Pollutant

TDG Exemption : Packages having a volumetric capacity of no more than 1.0L **Limited Quantities** and meeting the requirements of Transportation of Dangerous

Goods Part 1 Section 1.17 Limited Quantites are exempt from many of the TDG requirements for this classification. Each package must display the following limited quantity label.



Excelsior Epoxy Wet Set Adhesive

Version Revision Date: MSDS Number: Date of last issue: -

1.0 8/23/2016 EW-710 – Part B Date of first issue: 03/04/2016

SECTION 15. REGULATORY INFORMATION

US Federal Regulations

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
	Delayed (chronic) health hazard

Propanol, oxybis-, dibenzoate (27138-31-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Fatty acids, C18-unsaturated, dimers, polymers with tall-oil fatty acids and triethylenetetramine (68082-29-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Triethylenetetramine (112-24-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2,4,6-Tri(dimethylaminomethyl)phenol (90-72-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Tetraethylenepentamine (112-57-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

US State Regulations

Quartz (14808-60-7)	
U.S California - Proposition 65 -	WARNING: This product contains chemicals known
Carcinogens List	to the State of California to cause cancer.

Quartz (14808-60-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Triethylenetetramine (112-24-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Tetraethylenepentamine (112-57-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Canadian Regulations





: Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Class E - Corrosive Material



Excelsior Epoxy Wet Set Adhesive

Version Revision Date: MSDS Number: Date of last issue: -

1.0 8/23/2016 EW-710 – Part B Date of first issue: 03/04/2016

-	dibenzoate (27138-31-4)
	DSL (Domestic Substances List)
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Quartz (14808-60-7)	
	DSL (Domestic Substances List)
	IDL (Ingredient Disclosure List)
IDL Concentration 1 %	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Fatty acids, C18-unstriethylenetetramine	saturated, dimers, polymers with tall-oil fatty acids and e (68082-29-1)
Listed on the Canadian	DSL (Domestic Substances List)
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class E - Corrosive Material
Triethylenetetramin	e (112-24-3)
Listed on the Canadian	DSL (Domestic Substances List)
Listed on the Canadian	IDL (Ingredient Disclosure List)
IDL Concentration 0.1 9	%
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
	Class E - Corrosive Material
	ninomethyl)phenol (90-72-2)
Listed on the Canadian	DSL (Domestic Substances List)
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class E - Corrosive Material
Tetraethylenepenta	mine (112-57-2)
Listed on the Canadian	DSL (Domestic Substances List)
Listed on the Canadian	IDL (Ingredient Disclosure List)
IDL Concentration 1 %	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious
	toxic effects
	Class E - Corrosive Material

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and this SDS contains all of the information required by CPR.

SECTION 16. OTHER INFORMATION

Revision Date : 8.23.2016

Prepared By : RHC - 1602 N. Union St. Fostoria, OH 44830

P: (844) 393 - 4044 E: solutions@rhctechnical.com

Other Information : This document has been prepared in accordance with the

SDS requirements of OSHA Hazard Communication Standard

29 CFR 1910.1200.



Excelsior Epoxy Wet Set Adhesive

Version Revision Date: MSDS Number: Date of last issue: -

1.0 8/23/2016 EW-710 – Part B Date of first issue: 03/04/2016

GHS Full Text Phrases

GHS Code	GHS Phrase
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H411	Toxic to aquatic life with long lasting effects

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.