

VaraCore™ RIGID VINYL PLANK & TILE



SPECIFICATIONS: 4mm/12 mil

4mm/12 mil Plank:

- Nominal Dimensions: 7 1/4" x 47 3/4" x 4mm plank
- Finish: Embossed CRU 12 mil
- Quantity Per Carton: 10 planks
- Sq Ft Per Carton: 24.22 SF

4mm/12 mil Tile:

- Nominal Dimensions: 12" x 24" x 4mm tile
- Finish: Embossed CRU 12 mil
- Quantity Per Carton: 12 tiles
- Sq Ft Per Carton: 24 SF

WARRANTY

- 15-Year Residential/Multi-family Warranty
- 5-Year Limited Commercial Warranty



SPECIFICATIONS: 5mm/20 mil

5mm/20 mil Plank (attached pad):

- Nominal Dimensions: 7 1/4" x 47 3/4" x 5mm plank
- Finish: Embossed Next Gen 20 mil
- Quantity Per Carton: 8 planks
- Sq Ft Per Carton: 19.31 SF

5mm/20 mil Tile (attached pad):

- Nominal Dimensions: 12" x 24" x 5mm tile
- Finish: Embossed Next Gen 20 mil
- Quantity Per Carton: 10 tiles
- Sq Ft Per Carton: 20 SF

WARRANTY

- 20-Year Commercial Warranty



six degrees

FLOORING SURFACES™

931 South Springville Avenue • Fostoria, Ohio 44830

sixdegreesflooring.com • 844-432-5885

Technical FEATURES

- Easy to Maintain
- FloorScore® Certified
- 5mm/20 mil includes Next Generation Finish (GEN) – Improved durability over other ceramic urethane finishes
- Excellent Indentation Resistance
- Excellent Slip Resistance
- Excellent Chemical Resistance



CERTIFIED BY FSC GLOBAL SERVICES

- More durable than WPC – More flexible while maintaining compression strength to ease installation
- More stable than WPC – Better stability against temperature changes
- Waterproof
- Less floor undulation caused by uneven surface/subfloor imperfections
- More Eco-friendly – unlike WPC, there is no glue in our core, ensuring low VOCs

TEST INFORMATION

ASTM F 3261 – Class I, Type B, Backing Class A
Meets or exceeds recommendations
ASTM E 648 – Critical Radiant Flux: Class I, >.45 W/cm²
ASTM E 662 – Smoke Density: Pass
ASTM D 2047 – Slip Resistance: > 0.60
ASTM F 970 – Static Load Limit: Pass
ASTM F 925 – Chemical Resistance: Excellent (chart available)

Premium build
Made in the USA

For the most current and complete technical, installation and maintenance information, please visit sixdegreesflooring.com

VaraCore™ Planks • 7-1/4" x 47-3/4"



10.5"W x 7.25"H

VP312_C38G

Rio Grande



VPWP312_C38G

Rio Grande



7.25"W x 3.5"H

VP401_C22G / VPWP401_C22G

Colorado



VP312_C38 Rio Grande



VP401_C20G / VPWP401_C20G

Cumberland



VP208_C11G / VPWP208_C11G

Williamette



VP208_C11G Williamette



VP401_C21G / VPWP401_C21G

Tennessee



VP312_C04G / VPWP312_C04G

Yukon



VP232_C04G Wabash



VP232_C04G / VPWP232_C04G

Wabash



VP401_C23G / VPWP401_C23G

Ottawa



VP312_C35G Hudson



VPWP220_C12G Churchill



VP312_C36G / VPWP312_C36G

Cimarron



VP220_C12G / VPWP220_C12G

Churchill



VP312_C37G / VPWP312_C37G

Mississippi



VP312_C35G / VPWP312_C35G

Hudson



VPWP312_C37G Mississippi



VP233_C08G / VPWP233_C08G

Potomac

VaraCore™ Tiles • 12" x 24"



VT349_C01G / VTWP349_C01G

Connecticut



VT349_C01G Connecticut



VTWP362_C10G Missouri



VT362_C10G / VTWP362_C10G

Missouri