

Compass Colors™

VINYL FLOORING



six degrees
FLOORING SURFACES™



Des Moines CT205_C31,
Green Bay CT205_C33,
Boise CT205_C34,
Orlando CT205_C26,
Knoxville CT205_C24,
Cincinnati CT205_C27,
Baton Rouge CT205_C36

Des Moines CT205_C31,
Boise CT205_C34



Des Moines CT205_C31,
San Antonio CT205_C38,
Tulsa CT205_C35

Compass Colors™

VINYL FLOORING

Where will your design direction take you? Somewhere bold, bright and colorful? Then let the Compass Colors™ Collection lead the way. With 15 new beautiful colors, our Compass Colors™ Collection is great for schools, pediatrics, corporate... anywhere you want your floors to stand out or add a splash of color. Best of all, they're made here in the USA. It's a big world out there... we're here to help you make it more colorful. The Compass Colors™ Collection ... ***A Colorful Solution for Flooring Needs.***

you're



just



a



few




steps




away




Compass Colors™ Tiles • 12" x 24"




CT205_C38 San Antonio




CT205_C08 Pittsburgh




CT205_C31 Des Moines



CT205_C23 Vegas



CT205_C25 Charlotte



CT205_C34 Boise



CT205_C28 Atlanta




CT205_C37 Memphis




CT205_C36 Baton Rouge




CT205_C35 Tulsa




CT205_C33 Green Bay




CT205_C32 San Diego



CT205_C26 Orlando



CT205_C27 Cincinnati



CT205_C24 Knoxville

Technical

FEATURES

- Easy to Maintain
- Qualifies for LEED® Credits
- GREENGUARD Gold Certified
- Ceramic-Reinforced UV-Cured Finish
- Enhanced with EnviroSDTM Anti-Bacterial Agent
- Extremely Durable
- Excellent Indentation Resistance
- Excellent Chemical Resistance
- Excellent Slip Resistance
- 100% Recyclable



WARRANTY

- 20-Year Commercial Warranty

COMPASS COLORS™ TILE SPECIFICATIONS

Nominal Dimensions: 12" x 24" x 3 mm tile

Finish: Embossed 28 mil

Quantity Per Carton: 18 tiles (12" x 24")

Sq. Ft. Per Carton: 36 sq. ft./carton

TEST INFORMATION

ASTM F 1700 – Solid Vinyl Tile:

Class III, Type A& B

ASTM E 648 – Critical Radiant Flux:

Class I, >.45 W/cm²

ASTM E 662 – Smoke Density: Pass

ASTM D 2047 – Slip Resistance: > 0.60

ASTM F 970 – Static Load Limit: 250 PSI,
< .005" Indentation

ASTM F 925 – Chemical Resistance:
Excellent (chart available)

ASTM F 1515 – Light Stability: Pass



six degrees

FLOORING SURFACES™

931 South Springville Avenue • Fostoria, Ohio 44830

844-432-5885

For the most current and complete technical,
installation and maintenance information, please visit
sixdegreesflooring.com